

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
14 July 2005 (14.07.2005)

PCT

(10) International Publication Number
WO 2005/062797 A3

(51) International Patent Classification⁷: **A47G 1/06**

(21) International Application Number:
PCT/US2004/042503

(22) International Filing Date:
17 December 2004 (17.12.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
60/531,336 19 December 2003 (19.12.2003) US

(71) Applicant and

(72) Inventor: **SCHYMURA, Margarete** [US/US]; 2350
Broadway, New York, NY 10024 (US).


(74) Agent: **FALLER, F., Brice**; Cohen Pontani Lieberman &
Pavane, 551 Fifth Avenue, New York, NY 10176 (US).

(81) Designated States (*unless otherwise indicated, for every kind of national protection available*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (*unless otherwise indicated, for every kind of regional protection available*): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: PICTURE FRAME ASSEMBLY FOR MOUNTING TO A CYLINDRICAL OBJECT



(57) Abstract: A picture frame assembly includes a backing plate having a front surface, a rear surface, and a plurality of parallel grooves in one of the surfaces. The material and thickness of the backing plate are chosen so that the backing plate may be plastically deformed about a bending axis parallel to the grooves. At least one frame element, which may be formed integrally with the backing plate, is provided for retaining a planar picture element against the front surface of the backing plate. A pair of tack elements extending from the rear surface are provided for mounting the assembly to a cylindrical object such as a tree or a candle.

WO 2005/062797 A3



Published:

- with international search report
- before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(88) Date of publication of the international search report:

9 September 2005